



# MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

**Product number** 204-001  
**Product name** **Matte Fixative**  
**Effective date** 16-Sep-2011  
**Company information** Sprayway, Inc.  
1005 Westgate  
Addison, IL 60101 United States  
**Company phone** General Assistance 630-543-7600  
**Emergency telephone US** 800-424-9300  
**Emergency telephone outside US** 703-527-3887  
**Version #** 05  
**Supersedes date** 15-Jun-2011

## 2. Hazards Identification

**Emergency overview** Aerosol. EXTREMELY FLAMMABLE  
CONTENTS UNDER PRESSURE. Will be easily ignited by heat, spark or flames.  
Prolonged exposure may cause chronic effects.

**Potential health effects**

**Routes of exposure** Skin contact. Ingestion.

**Eyes** Contact with eyes may cause irritation.

**Skin** Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**Inhalation** Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

**Ingestion** Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

**Target organs** Central nervous system. Lungs.

**Chronic effects** May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage. Prolonged skin contact may defat the skin and produce dermatitis.

**Signs and symptoms** Discomfort in the chest. Narcosis. Defatting of the skin. Irritation.

## 3. Composition / Information on Ingredients

Components	CAS #	Percent
Methylal	109-87-5	30 - 40
Acetone	67-64-1	20 - 30
n-Butane	106-97-8	20 - 30
Propane	74-98-6	8 - 10
VM&P Naphtha	8032-32-4	5 - 8
Isopropyl Alcohol	67-63-0	3 - 5
Non-hazardous and other components below reportable levels		2.5 - 10

## 4. First Aid Measures

### First aid procedures

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

**Skin contact** Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.

**Inhalation**  
**Ingestion**

Move to fresh air. If symptoms persist, get medical attention.

If material is ingested, immediately contact a poison control center. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

**Notes to physician**

Symptoms may be delayed.

## 5. Fire Fighting Measures

**Flammable properties**

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

**Extinguishing media**

**Suitable extinguishing media**

Alcohol foam. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Do not use water jet.

**Protection of firefighters**

**Protective equipment and precautions for firefighters**

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

## 6. Accidental Release Measures

**Methods for containment**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.

**Methods for cleaning up**

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

## 7. Handling and Storage

**Handling**

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.

**Storage**

Level 3 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

## 8. Exposure Controls / Personal Protection

**Exposure limits**

**ACGIH**

**Components**

**CAS #**

**TWA**

**STEL**

**Ceiling**

Methylal	109-87-5	1000 ppm	Not established	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
VM&P Naphtha	8032-32-4	300 ppm	Not established	Not established
Isopropyl Alcohol	67-63-0	200 ppm	400 ppm	Not established

**OSHA**

Components	CAS #	TWA	STEL	Ceiling
Methylal	109-87-5	1000 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Isopropyl Alcohol	67-63-0	400 ppm	Not established	Not established

**Personal protective equipment**

<b>Eye / face protection</b>	Wear chemical goggles.
<b>Skin protection</b>	Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing.
<b>Respiratory protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

<b>9. Physical &amp; Chemical Properties</b>
--

<b>Appearance</b>	Compressed liquefied gas.
<b>Boiling point</b>	86 °F (30 °C) estimated
<b>Color</b>	Yellow.
<b>Density</b>	0.7292 g/cm <sup>3</sup> estimated
<b>Flammability (HOC)</b>	41.047 kJ/g estimated
<b>Flash back</b>	Yes
<b>Flash point</b>	-156 °F (-104.4 °C) Propellant
<b>Form</b>	Aerosol.
<b>Freezing point</b>	Not available
<b>Odor</b>	None known.
<b>pH</b>	Not applicable
<b>Physical state</b>	Liquid.
<b>Pressure</b>	30 - 50 psig @ 70F
<b>Solubility</b>	Partially
<b>Specific gravity</b>	0.7293

<b>10. Chemical Stability &amp; Reactivity Information</b>
--

<b>Chemical stability</b>	Risk of ignition.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

<b>11. Toxicological Information</b>
--------------------------------------

<b>Acute effects</b>	Acute LD50: 21740 mg/kg estimated, Rat, Dermal
<b>Component analysis - LD50</b>	
<b>Toxicology Data - Selected LD50s and LC50s</b>	
Acetone	67-64-1 Oral LD50 Rat 5800 mg/kg
Isopropyl Alcohol	67-63-0 Inhalation LC50 Rat 72.6 mg/L 4 h; Oral LD50 Rat 4396 mg/kg; Dermal LD50 Rat 12800 mg/kg; Dermal LD50 Rabbit 12870 mg/kg
Methylal	109-87-5 Inhalation LC50 Mouse 57 g/m <sup>3</sup> 7 h; Oral LD50 Rat 6653 mg/kg
n-Butane	106-97-8 Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6 Inhalation LC50 Rat 658 mg/L 4 h
VM&P Naphtha	8032-32-4 Inhalation LC50 Rat 3400 ppm 4 h
<b>Sensitization</b>	Not expected to be hazardous by OSHA criteria.
<b>Teratogenicity</b>	Not expected to be hazardous by OSHA criteria.

## 12. Ecological Information

<b>Ecotoxicity</b>	Components of this product have been identified as having potential environmental concerns.  LC50 10042 mg/L estimated, Fish, 96.00 Hours, EC50 43751 mg/L estimated, Daphnia, 48.00 Hours, IC50 21660 mg/L estimated, Algae, 72.00 Hours,
--------------------	--

## 13. Disposal Considerations

<b>Waste codes</b>	D001: Waste Flammable material with a flash point <140 F
<b>Disposal instructions</b>	Contents under pressure. Dispose of this material and its container at hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

## 14. Transport Information

### Department of Transportation (DOT) Requirements

#### Basic shipping requirements:

<b>Proper shipping name</b>	Consumer commodity
<b>Hazard class</b>	ORM-D
<b>Subsidiary hazard class</b>	None
<b>Additional information:</b>	
<b>Packaging exceptions</b>	156, 306
<b>Packaging non bulk</b>	156, 306
<b>Packaging bulk</b>	None

### IMDG

#### Basic shipping requirements:

<b>Proper shipping name</b>	AEROSOLS
<b>Hazard class</b>	2.1
<b>UN number</b>	1950
<b>Additional information:</b>	
<b>Packaging exceptions</b>	LTD QTY
<b>Item</b>	5F
<b>Labels required</b>	None
<b>Transport Category</b>	2



### IATA

#### Basic shipping requirements:

<b>Proper shipping name</b>	Aerosols, flammable
<b>Hazard class</b>	2.1
<b>UN number</b>	1950
<b>Additional information:</b>	
<b>Packaging exceptions</b>	LTD QTY
<b>Labels required</b>	2.1



## 15. Regulatory Information

<b>US federal regulations</b>	OSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly Hazardous Process Safety Standard, 29 CFR 1910.119. This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
-------------------------------	---

#### U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Isopropyl Alcohol	67-63-0	1.0 % de minimis concentration (only if manufactured by the strong acid process, no supplier notification)
-------------------	---------	--

**Occupational Safety and Health Administration (OSHA)**

29 CFR 1910.1200 hazardous chemical Yes

**CERCLA (Superfund) reportable quantity**

Acetone: 5000.0000

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - Yes  
 Reactivity Hazard - No

**Inventory status**

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**State regulations****U.S. - Pennsylvania - RTK (Right to Know) List**

Acetone	67-64-1	Environmental hazard
Isopropyl Alcohol	67-63-0	Environmental hazard
Methylal	109-87-5	Present
n-Butane	106-97-8	Present
Propane	74-98-6	Present
VM&P Naphtha	8032-32-4	Present

**16. Other Information****Further information**

HMIS® is a registered trade and service mark of the NPCA.

**HMIS® ratings**

Health: 1\*  
 Flammability: 4  
 Physical hazard: 0

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**MSDS sections updated**

Product and Company Identification: Product Review  
 Handling and Storage: Storage  
 Exposure Controls / Personal Protection: Skin and body protection  
 Transport Information: Product Shipping Name/Packing Group

**Prepared by**

Regulatory Compliance