



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 753
Product name Auto Care Wax & Shine
Effective date 24-Jan-2012
Company information Sprayway, Inc.
1005 Westgate
Addison, IL 60101 United States
Company phone 1-630-543-7600
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 04
Supersedes date 13-Apr-2010
Product use Wax.

2. Hazards Identification

Emergency overview Aerosol. CONTENTS UNDER PRESSURE.
Will be easily ignited by heat, spark or flames. Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Ingestion.

Eyes Contact with eyes may cause irritation.

Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. Components of the product may be absorbed into the body by ingestion.

Target organs Kidneys. Central nervous system. Lungs.

Chronic effects Kidney injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Narcosis. Coughing. Defatting of the skin.

3. Composition / Information on Ingredients

Components	CAS #	Percent
1,1-Difluoroethane	75-37-6	15 - 20
Aliphatic Hydrocarbons	8052-41-3	10 - 15
Aluminum Silica	66402-68-4	1 - 3
Non-hazardous and other components below reportable levels		60 - 80

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off with warm water and soap. Remove and isolate contaminated clothing and shoes. Get medical attention if irritation develops and persists.

Inhalation If symptoms develop move victim to fresh air. If inhalation of gas/fume/vapor/dust/mist from the material is excessive (air concentration is greater than the TLV or health effects are noticed), immediately remove the affected person(s) to fresh air. Get medical attention if symptoms persist.

Ingestion

Do not induce vomiting without advice from poison control center. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Notes to physician

Symptoms may be delayed.

5. Fire Fighting Measures

Flammable properties

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media**Suitable extinguishing media**

Water. Alcohol foam. Dry chemical. Carbon dioxide (CO2).

Protection of firefighters**Protective equipment and precautions for firefighters**

In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up. Cool containers with flooding quantities of water until well after fire is out.

6. Accidental Release Measures

Methods for containment

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area thoroughly with water.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 3 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits**ACGIH****Components****CAS #****TWA****STEL****Ceiling**

Aliphatic Hydrocarbons

8052-41-3

100 ppm

Not established

Not established

OSHA**Components****CAS #****TWA****STEL****Ceiling**

Aliphatic Hydrocarbons

8052-41-3

500 ppm

Not established

Not established

Personal protective equipment**Eye / face protection**

Chemical goggles are recommended. Not normally needed.

Skin protection

Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties
--

Appearance

Compressed liquefied gas.

Boiling point	149 °F (65 °C) estimated
Color	Colorless.
Density	0.9551 g/cm3 estimated
Flammability (HOC)	36.22 kJ/g estimated
Flash back	No
Flash point	-58 °F (-50 °C) estimated
Form	Aerosol.
Freezing point	Not available
Odor	Characteristic.
pH	6.5 - 7.5
Physical state	Liquid.
Pressure	65 - 75 psig @ 70F
Solubility	Insoluble
Specific gravity	0.9552 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include oxides of carbon.

11. Toxicological Information

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

1,1-Difluoroethane 75-37-6 Inhalation LC50 Mouse 977 g/m3 2 h

Sensitization	Not expected to be hazardous by OSHA criteria.
Teratogenicity	Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity	LC50 500 mg/L, Fish, 96.00 Hours, Components of this product are hazardous to aquatic life.
--------------------	--

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Aerosols
Hazard class	2.1
UN number	UN1950

Additional information:

Special provisions	153, N82
Packaging exceptions	LTD QTY
Packaging non bulk	None
Packaging bulk	None

Further information	Until 12/31/2013, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/13 and may be used now in place of the "Consumer Commodity ORM-D" marking but not concurrently.
----------------------------	--



IMDG**Basic shipping requirements:**

Proper shipping name AEROSOLS
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Labels required None

**IATA****Basic shipping requirements:**

Proper shipping name Aerosols, flammable
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Labels required 2.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Aluminum Silica 66402-68-4 1.0 % de minimis concentration (dust or fume only)

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Aluminum Silica: 1000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Aliphatic Hydrocarbons 8052-41-3 Present
 Aluminum Silica 66402-68-4 Environmental hazard

16. Other Information

Further information

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*
Flammability: 4
Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

MSDS sections updated

Product and Company Identification: Product Review
Hazards Identification: Eyes
Transport Information: Product Shipping Name/Packing Group
Transport Information: Further information

Prepared by

Regulatory Compliance