



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 765-001
Product name Industrial Premium Grease
Effective date 14-Mar-2011
Company information Sprayway, Inc.
1005 Westgate
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 05
Supersedes date 10-Aug-2009

2. Hazards Identification

Emergency overview Will be easily ignited by heat, spark or flames. EXTREMELY FLAMMABLE CONTENTS UNDER PRESSURE. Aerosol. Irritating to skin. Irritating to eyes. Irritating to respiratory system. Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Inhalation. Skin contact.

Eyes Causes eye irritation.

Skin Irritating to skin.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Irritating to respiratory system. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.

Target organs Central nervous system. Respiratory system.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage.

Signs and symptoms Discomfort in the chest. Narcosis.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Aliphatic Petroleum Solvent	64742-89-8	40 - 50
Propane	74-98-6	15 - 20
Non-hazardous and other components below reportable levels		20 - 40

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.

Skin contact Wash off immediately with plenty of water. Remove and isolate contaminated clothing and shoes. If skin irritation persists, call a physician.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Call a physician if symptoms develop or persist.

Ingestion Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician Symptoms may be delayed.

5. Fire Fighting Measures

Flammable properties	Vapor or gas may spread to distant ignition sources and flash back.
Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical. Carbon dioxide (CO2). Halons.
Protection of firefighters	
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Protective equipment and precautions for firefighters	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.
Methods for cleaning up	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not breathe gas/fumes/vapor/spray. Avoid contact with skin. Avoid contact with eyes. Wear personal protective equipment. Avoid prolonged exposure.
Storage	Level 2 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Wear chemical goggles.
Skin protection	Wear appropriate chemical resistant clothing. Protective gloves.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	93.2 °F (33.9 °C) estimated
Color	Gold.
Density	0.7169 g/cm ³ estimated
Flammability (HOC)	27.71 kJ/g
Flash back	Yes
Flash point	-156 °F (-104.4 °C) estimated

Form	Liquid. Aerosol.
Freezing point	Not available
Odor	Solvent.
pH	Not applicable
Physical state	Liquid.
Pressure	35 - 45 psig @ 70F
Solubility	Partially
Specific gravity	0.717 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition. Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Isocyanates. Strong oxidizing agents.
Hazardous decomposition products	Irritants. Toxic gas. May include oxides of oxides of carbon.

11. Toxicological Information

Acute effects	Acute LD50: 6903 mg/kg estimated, Rat, Dermal Acute LC50: 1339 mg/l/4h estimated, Rat, Inhalation
----------------------	--

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Aliphatic Petroleum Solvent	64742-89-8	Oral LD50 Mouse 5000 mg/kg; Dermal LD50 Rabbit 3000 mg/kg
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

Sensitization	Not expected to be hazardous by OSHA criteria.
Teratogenicity	Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity	LC50 18.06 mg/L, Fish, 96.00 Hours, EC50 1266 mg/L, Daphnia, 48.00 Hours, IC50 10815 mg/L, Algae, 72.00 Hours, Components of this product have been identified as having potential environmental concerns.
--------------------	---

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG**Basic shipping requirements:**

Proper shipping name AEROSOLS
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Item 5F
Labels required None
Transport Category 2

**IATA****Basic shipping requirements:**

Proper shipping name Aerosols, flammable
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Labels required 2.1



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No
Section 311 hazardous chemical Yes
Hazard categories (311/312) Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Aliphatic Petroleum Solvent	64742-89-8	Present
Propane	74-98-6	Present

16. Other Information

Further information HMIS Trademark Statement

HMIS® ratings Health: 1*
 Flammability: 3
 Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MSDS sections updated

Product and Company Identification: Product and Company Identification

Prepared by

Regulatory Compliance