



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 945
Product name **Silicone Spray**
Effective date 17-Apr-2008
Company information Sprayway, Inc.
484 Vista Ave.
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 04
Supersedes date 06-Dec-2007

2. Hazards Identification

Emergency overview Aerosol. EXTREMELY FLAMMABLE
CONTENTS UNDER PRESSURE.
Pressurized container may explode when exposed to heat or flame.

OSHA regulatory status Harmful in contact with eyes. Prolonged exposure may cause chronic effects.
This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects

Eyes Contact may irritate or burn eyes. Eye contact may result in corneal injury.

Skin Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

Target organs Central nervous system. Respiratory system.

Chronic effects Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage.

Signs and symptoms Discomfort in the chest. Corneal damage. Narcosis. Conjunctivitis. Defatting of the skin. Irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Propane	74-98-6	40 - 50
n-Pentane	109-66-0	40 - 50
Non-hazardous and other components below reportable levels		2.5 - 10

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.

Skin contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Ingestion Rinse mouth. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician Symptoms may be delayed.

General advice

Call a physician if symptoms develop or persist.

5. Fire Fighting Measures**Flammable properties**

Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back.

Extinguishing media**Suitable extinguishing media**

Water. Water spray. Water fog. Foam. Dry chemical. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters**Protective equipment and precautions for firefighters**

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Cool containers with flooding quantities of water until well after fire is out.

6. Accidental Release Measures**Personal precautions**

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel away.

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift.

Methods for cleaning up

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly. After removal flush contaminated area thoroughly with water.

7. Handling and Storage**Handling**

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.

Storage

Level 3 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children. Use care in handling/storage.

8. Exposure Controls / Personal Protection**Exposure limits****ACGIH****Components****CAS #****TWA****STEL****Ceiling**

Propane

74-98-6

1000 ppm

Not established

Not established

n-Pentane

109-66-0

600 ppm

Not established

Not established

OSHA**Components****CAS #****TWA****STEL****Ceiling**

Propane

74-98-6

1000 ppm

Not established

Not established

n-Pentane

109-66-0

1000 ppm

Not established

Not established

Engineering controls

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Personal protective equipment**Eye / face protection**

Wear chemical goggles.

Skin protection

Wear appropriate chemical resistant gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General hygiene considerations

When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Appearance	Not available
Boiling point	-13 °F (-25 °C) estimated
Color	Colorless.
Flammability (HOC)	42.31 kJ/g estimated
Flash back	Yes
Flash point	-156 °F (-104.4 °C) estimated
Form	Aerosol.
Odor	Solvent.
pH	Not applicable
Physical state	Liquid.
Pressure	57 - 67 psig @ 70F
Solubility	None
Specific gravity	0.5702 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition. Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	May include oxides of nitrogen.

11. Toxicological Information

Acute effects	Acute LD50: 6253 mg/kg estimated, Rat, Dermal Acute LC50: 60000 mg/l/4h estimated, Rat, Inhalation
Sensitization	Not expected to be hazardous by OSHA criteria.
Local effects	Contact may irritate or burn eyes. Components of the product may be absorbed into the body through the skin.
Chronic effects	Hazardous by OSHA criteria. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged or repeated exposure may cause lung injury. Prolonged exposure may cause chronic effects.
Mutagenicity	Not expected to be hazardous by OSHA criteria.
Reproductive effects	Not expected to be hazardous by OSHA criteria.
Teratogenicity	Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity	LC50 23.29 mg/L estimated, Fish, 96.00 Hours, EC50 9.32 mg/L estimated, Daphnia, 48.00 Hours, Components of this product have been identified as having potential environmental concerns.
-------------	---

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG**Basic shipping requirements:**

Proper shipping name AEROSOLS, flammable
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Item 5F
Labels required 2.1
Transport Category 2

**IATA****Basic shipping requirements:**

Proper shipping name Aerosols, flammable
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
 All components are on the U.S. EPA TSCA Inventory List.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Chemical	Inventory Number	Present
n-Pentane	109-66-0	Present
Propane	74-98-6	Present

16. Other Information

HMIS® ratings

Health: 1*
 Flammability: 4
 Physical hazard: 0
 Personal protection: X

Prepared by

Regulatory Compliance

trade_name Silicone Spray

Product #: 945 Revision date: 17-APR-2008 Print date: 17-APR-2008

MSDS US

4 / 5

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date

17-Apr-2008

MSDS sections updated

Transport Information: Product Shipping Name/Packing Group