



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 1052_252
Material name Aci bHJb'5 Jf' HcIU' F'YUgY' Blast Out
Revision date 09-03-2013
Company information Sprayway, Inc.
1005 S. Westgate Drive
Addison, IL 60101 United States
Company phone General Assistance 1-630-628-3000
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 02
Supersedes date 09-03-2013

2. Hazards Identification

Emergency overview DANGER

CONTENTS UNDER PRESSURE.
Aerosol. Pressurized container may explode when exposed to heat or flame. May cause flash fire or explosion.

Will be easily ignited by heat, spark or flames. Harmful in contact with eyes. Prolonged exposure may cause chronic effects.

OSHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
Potential health effects
Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.
Eyes Eye contact may result in corneal injury. Contact with eyes may cause irritation.
Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.
Ingestion Exposure by ingestion of an aerosol is unlikely. Components of the product may be absorbed into the body by ingestion.
Target organs Central nervous system. Respiratory system.
Chronic effects Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Signs and symptoms Corneal damage. Narcosis. Decrease in motor functions. Behavioral changes. Conjunctivitis. Skin irritation. Defatting of the skin. Rash.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Acetone	67-64-1	60 - 80
Butane	106-97-8	10 - 20
Propane	74-98-6	10 - 20
Other components below reportable levels		2.5 - 10

4. First Aid Measures

First aid procedures
Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Skin contact Wash off with warm water and soap. Get medical attention if irritation develops and persists.

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth thoroughly.
Notes to physician	Symptoms may be delayed.
General advice	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible).
5. Fire Fighting Measures	
Flammable properties	Flammable by OSHA criteria. Heat may cause the containers to explode. Vapors may travel considerable distance to a source of ignition and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media	Powder. Alcohol resistant foam. Water. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Protection of firefighters	
Protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental Release Measures

Personal precautions	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the MSDS.
Environmental precautions	Do not contaminate water.
Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Prevent entry into waterways, sewer, basements or confined areas.
Methods for cleaning up	Should not be released into the environment. Stop the flow of material, if this is without risk. Isolate area until gas has dispersed. Following product recovery, flush area with water. For waste disposal, see section 13 of the MSDS.

7. Handling and Storage

Handling	Vapors may form explosive mixtures with air. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. Use only in area provided with appropriate exhaust ventilation.
Storage	Contents under pressure. The pressure in sealed containers can increase under the influence of heat. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Use care in handling/storage. Store away from incompatible materials (see Section 10 of the MSDS). Level 3 Aerosol.

8. Exposure Controls / Personal Protection

Occupational exposure limits

ACGIH Biological Exposure Indices Components

Components	Type	Value
Acetone (CAS 67-64-1)	BEI	50 mg/l

US. ACGIH Threshold Limit Values Components

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3
		1000 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm

Engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Eye / face protection

Do not get in eyes. Wear safety glasses with side shields (or goggles).

Skin protection

Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Properties

Appearance	Not available.
Auto-ignition temperature	825.78 °F (440.99 °C) estimated
Boiling point	95.66 °F (35.37 °C) estimated
Color	Not available.
Flammability limits in air, upper, % by volume	8.5 % estimated
Flammability limits in air, lower, % by volume	2.1 % estimated
Flash point	-156.00 °F (-104.44 °C) Propellant estimated
Form	Aerosol.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Physical state	Gas.
Solubility (water)	Not available.
Specific gravity	0.7 estimated
Vapor pressure	50.47 psig @70F estimated
Other data	
Heat of combustion	32.49 kJ/g estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Hazardous decomposition products No hazardous decomposition products are known.
Possibility of hazardous reactions Hazardous polymerization does not occur.

11. Toxicological Information

Toxicological data

Product	Species	Test Results
Blast Out Mountain Air Odor Bomb (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	28568.7344 mg/kg, estimated 28.5687 ml/kg, estimated
<i>Inhalation</i>		
LC50	Mouse	5787.2339 mg/l, 2 Hours, estimated
	Rat	10889.4111 mg/l, 15 Minutes, estimated 5600 mg/l, 4 Hours, estimated 2632 mg/l/4h, estimated 71.5647 mg/l, 8 Hours, estimated
<i>Oral</i>		
LD50	Mouse	4285.3101 mg/kg, estimated
	Rabbit	7627.8521 mg/kg, estimated
	Rat	8284.9336 mg/kg, estimated
<i>Other</i>		
LD50	Mouse	1852.6825 mg/kg, estimated
	Rat	7856.4023 mg/kg, estimated
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	20000 mg/kg 20 ml/kg
<i>Inhalation</i>		
LC50	Rat	76 mg/l, 4 Hours 50.1 mg/l, 8 Hours
<i>Oral</i>		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
<i>Other</i>		
LD50	Mouse	1297 mg/kg
	Rat	5500 mg/kg
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 1442.847 mg/l, 15 Minutes

Components	Species	Test Results
		658 mg/l/4h

* Estimates for product may be based on additional component data not shown.

Local effects Components of the product may be absorbed into the body through the skin. Contact may irritate or burn eyes.

Chronic effects Hazardous by OSHA criteria. Prolonged inhalation may be harmful. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.

Carcinogenicity

ACGIH Carcinogens

Acetone (CAS 67-64-1) A4 Not classifiable as a human carcinogen.

Neurological effects Hazardous by OSHA criteria.

Further information Symptoms may be delayed.

12. Ecological Information

Ecotoxicological data

Product	Species	Test Results
Blast Out Mountain Air Odor Bomb (CAS Mixture)		
Crustacea	EC50 Daphnia	7367.5908 mg/l, 48 hours, estimated
Fish	LC50 Fish	12050.1338 mg/l, 96 hours, estimated

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50 Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Ecotoxicity Contains a substance which causes risk of hazardous effects to the environment.

Environmental effects An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Persistence and degradability Not available.

Bioaccumulation / Accumulation

Bioaccumulative potential

Octanol/water partition coefficient log Kow

Acetone	-0.24
Butane	2.89
Propane	2.36

Partition coefficient

Acetone	-0.24
Butane	2.89
Propane	2.36

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1) U002

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport Information

DOT

Basic shipping requirements:

UN number	UN1950
Proper shipping name	Aerosols, flammable
Hazard class	2.1
Special precautions	Read safety instructions, MSDS and emergency procedures before handling.
Additional information:	
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2013, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/13 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Labels required	2.1
ERG code	10L
Special precautions for user	Read safety instructions, MSDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
Labels required	None
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
Packaging Exceptions	LTD QTY

DOT



IATA; IMDG



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 150 kg by weight
50 gallons by volume
6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 % weight/volumn

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA (Superfund) reportable quantity

Acetone: 5000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

Section 302 extremely hazardous substance No

SARA 311/312 Hazardous chemical No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

State regulations California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - New Jersey RTK - Substances: Listed substance

Acetone (CAS 67-64-1) Listed.
Butane (CAS 106-97-8) Listed.
Propane (CAS 74-98-6) Listed.

US. Pennsylvania RTK - Hazardous Substances

Acetone (CAS 67-64-1) Listed.
Butane (CAS 106-97-8) Listed.
Propane (CAS 74-98-6) Listed.

16. Other Information

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.