

SW077 All Purpose Dry Lubricant & Release Agent

- **DESCRIPTION:** The dry lubricant & release agent stops sticking and retards corrosion. This silicone spray eliminates annoying squeaks in hinges, latches, springs, etc. It leaves no greasy or oily film and is not affected by water or oil. The heat stable formula will not freeze or melt.
- **USES:** It protects battery terminals, tools, aluminum windows and doors. An excellent release agent for plastic injection and compression moldings. Use on any surface: metal glass rubber plastic painted surfaces fabrics.

SPECS:	Can Size:	20.07	
01 200.	Net Weight:		
-	Shipping Weight:		
-		12 cans per case	
-	v	0 41911 00077 2	Sprayway
-			
PHYSICAL	Color:	Colorless	SW-077
CHARACTERISTICS:	Fragrance:	Solvent	DRY LUBRICANT &
	Shelf Life:	1 Year +	abrifiant Sec Général Et Agent Anti-Grippage
			STOPS STICKING
REGULATORY:	Ozone Depleting Compounds:	None	HEAT STABLE
	Recyclable Packaging:	Yes	RETARDS CORROSION RETARDS CORROSION
	VOC Compliant CARB/OTC:	Yes	RETAILLE ENDER
	CPSC Flammability:	Required to be labeled as extremely flammable per 16 CFR 1500	DANGER: EXTREMELY FLAMMABLE
-	24 HOUR MEDICAL EMERGENCY:	1-866-836-8855	HARMFUL OR FATAL IF SWALLOWED. Eye and skin irritants. Contents under pressure.
PRODUCT FEATURES:	 Fast drying Leaves no greasy or oily film Heat stable - will not freeze or melt Use on any surface 		Read carefully other caudions on back panel. DANGER: EXTREMEMENT INFLAMMARE IST NODE ET PEUT ETRE MORTEL D'AVAG IST NODE ET PEUT ETRE MORTEL D'AVAG IST NODE ET PEUT ETRE MORTEL D'AVAG CONTENU SOUS PRESSION. UN alterivement is a autres mass en garde qui a terment auto is loca artrite. NET WT. / POIDS NET: 12 OZ (340 g)