

## SW633 RTV Silicone Caulk Marker Red

- **DESCRIPTION:** This R.T.V. Sealant Adhesive is an instant gasket maker, replaces a wide range of cork, paper, asbestos, felt and metal gaskets. Has excellent adhesion characteristics, high chemical resistance and will not sag or shrink. Withstands intermittent temperatures up to 500°F and pressures up to 330 psi. Offers unmatched performance under the most severe operating conditions. Virtually unaffected by chemical deterioration, extreme weather, temperature or aging.
- **USES:** FORMS IN-PLACE GASKETS and SEALS FOR: Pumps, High Pressure Pipe Joints, Oil and Transmission Pans, Oil and Water Pumps, Valve and Timing Chain Covers, Electric Motors and Electrical Control Boxes, Gear Boxes, Compressors, Machine Covers, Rigid Flange Assemblies, Equipment Housings. This product meets the requirement of FDA Regulation 21 CFR 177.2600, when fully cured and washed.

SPECS:	Can Size:	8 oz.	
	Net Weight:	8 oz.	
	Shipping Weight:	4.368 lbs.	
	Packaged:	6 cans per case	
	UPC Number:	0 41911 00633 0	
PHYSICAL	Color:	Red	(Sprayway <sub>®</sub> )
CHARACTERISTICS:	Fragrance:	Solvent	
	Shelf Life:	1 Year +	SW-633
			RTV
<b>REGULATORY:</b>	Recyclable Packaging:	Yes	SILICONE CAULK MARKE
	VOC Compliant CARB/OTC:	Yes	RED
	CPSC Flammability:	Flammable	SEALS, BONDS, INSULATES
	24 HR. MEDICAL EMERGENCY:	1-866-836-8855	ECONOMICAL - ELIMINATES WASTE ECONOMICAL - ELIMINATES WASTE WATERPROOF - WEATHERPROOF
FEATURES:	<ul> <li>SEALS, BONDS, INSULATES</li> <li>LOW VOLATILE • FLEXIBLE</li> <li>ECONOMICAL • ELIMINATES</li> <li>WATERPROOF • WEATHERP</li> </ul>	5 WASTE	EIMINATES SOLECTION CONTROL ON CONTROL OF CONTROL DO TLOW YOLATLE R.T.V. SILCOME MEETS ON AND OE N. SPECIFICATIONS SAFET ON CONTROL ON CONTROL EDUIPPED VENICES SOLECTION OF CONTROL PRESSING SEMANESTICS SEE ON SHARE GASKET INSTANLING REMAINS SEMANESTICS FTO SOLECTION EIMINATES NEED TO STOCK EIMINATES NEED TO STOCK CONVENTIONAL GASKETS AND GALS CONVENTIONAL GASKETS AND SALS CONVENTIONAL GASKETS AND SALS
			WARNING: CONTACT WITH UNCURED SEALANT C Irritation. Contents under pressure of Container is pressurized with a flamm Hydrofluorocarbon propellant. Od Not Re Bibber Duid Doctron of Container

**REORDER/ITEM NUMBER SW-633** 

Manufactured by: SPRAYWAY, INC. 2651 Warrenville Rd. Ste 300 | Downers Grove, IL 60515

PLEASE RECYCLE

SOURCED

2651 Warrenville Rd. Ste 300 | Downers Grove, IL 60515 800-332-9000 • Fax: 630-543-7797 • www.spraywayinc.com