

PRODUCT TECHNICAL DATA SHEET

SW659 RTV Silicone Caulk Marker Clear

DESCRIPTION: This R.T.V. Silicone Caulk and Sealant is ideal for use wherever a strong permanently

> elastic weatherproof caulk, sealant or adhesive is needed. Designed to seal non-porous surfaces around ceramic tile, cultured marble, showers, tubs, sinks and plumbing fixtures. Ideal for caulking windows, doors, sills and ceiling cracks and crevices. Features excellent adhesion and high chemical resistance. Will not sag or shrink during severe

temperature changes.

Useful for sealing cracks in machinery, heating and ventilation duct work, plumbing **USES:**

fixtures, electrical connections and low pressure water and drain lines. Bonds

nameplates, machinery flanges, glass, signs, electrical insulation etc. Offers unmatched performance under the most severe conditions. Remains flexible and will not shrink.

crack, crumble or dry out.

Net Weight: 8 oz.

Shipping Weight: 4.368 lbs.

Packaged: 6 cans per case

UPC Number: 0 41911 00659 0

PHYSICAL CHARACTERISTICS:

Color: Clear

Fragrance: Solvent

Shelf Life: 1 Year +

REGULATORY:

Recyclable Packaging: Yes

VOC Compliant CARB/OTC:

CPSC Flammability: Not required to be listed

as flammable

24 HR. MEDICAL EMERGENCY: 1-866-836-8855

FEATURES:

- SEALS, BONDS, INSULATES
- FLEXIBLE EASY TO USE
- WATERPROOF WEATHERPROOF
- SEALS WINDOWS, DOORS, TILE, MARBLE, ETC.





Manufactured by: SPRAYWAY, INC.

REORDER/ITEM NUMBER SW-659

Sprayway

SEALS, BONDS, INSULATES

WAVERPROOF > WEAVHERPROOF

FLEXIBLE FROM -30°F 10 0500° CAULKS TUES, SINKS, SHOWERS AND PRUMBING FIXTURES SEALS WINDOWS, DOORS, TILE, MARBLE, ETC.

BONDS ALMOST ANY MATERIAL

WARNING: CONTACT WITH UNCURED SEALANT CAUSE

IRRITATION. CONTENT WITH UNCURED SEALANI CAUSAIRRITATION. CONTENTS UNDER PRESSURE. OUTER
CONTAINER IS PRESSURIZED WITH A FLAMMABLE
PUBORLUGBOCARBON PROPELLANT. DO NOT RENOVE
RUBBER PLUG IN BOTTOM OF CONTAINER.
SEE OTHER CAUTIONS ON BACK PAREL.
NET WT. 8 OZ (227 g)

FLEXIBLE

EASY TO USE