



SW465 Anti-Seize Compound

DESCRIPTION: Contains No Chlorinated Solvents (No 1,1,1-Trichloroethane). Prevents galling, seizing, pitting, fretting, corrosion and distortion of threaded, keyed, splined and press fitted assemblies. Protects at sustained temperatures of up to 2100°F. Highly resistant to moisture, weather, chemical fumes, salt spray and steam. Allows tighter, more vibration-proof seals using less torque while making disassembly easier.

USES: Industrial machinery, construction, farm, mining and earth moving equipment, marine hardware, vehicle fleets and assembly lines.

SPECS:	Can Size: 16 oz.
	Net Weight: 12 oz.
	Shipping Weight: 12.6 lbs
	Packaged: 12 cans per case
	UPC Number: 0 41911 00465 7

PHYSICAL CHARACTERISTICS:	Color: Grey
	Fragrance: Solvent
	Spray Pattern: 2.50" circle @ 8"
	Shelf Life: 1 Year +

REGULATORY:	Recyclable Packaging: Yes
	VOC Compliant CARB/OTC: Yes
	CPSC Flammability: Extremely Flammable
	24 HR. MEDICAL EMERGENCY: 1-866-836-8855

- FEATURES:**
- NON-CHLORINATED
 - EXTREME TEMPERATURE & EXTREME PRESSURE LUBRICANT



REORDER/ITEM NUMBER SW-465



Manufactured by:
SPRAYWAY, INC.
 2651 Warrenville Rd. Ste 300 | Downers Grove, IL 60515
 800-332-9000 • Fax: 630-543-7797 • www.spraywayinc.com