



### SW689 Penetrating Lubricant with PTFE

**DESCRIPTION:** Contains no silicones or chlorinated solvents which affect plastics, lacquers, insulation and paint. Contains Molybdenum disulfide and polytetrafluoroethylene for added pressure and wear resistance. Forceful jet-spray aids in rapid penetration through rust and corrosion to free frozen parts. Leaves a long-lasting, lubricating film which defends against future corrosion.

**USES:** Provides effective lubrication over a broad range of temperatures and pressures.  
\*NOTE: SPECIAL VALVE ALLOWS CAN TO BE SPRAYED WHILE HELD IN ANY POSITION.

<b>SPECS:</b>	Can Size: 16 oz.
	Net Weight: 11 oz.
	Shipping Weight: 16.2 lbs.
	Packaged: 12 cans per case
	UPC Number: 7 69848 50689 0

<b>PHYSICAL CHARACTERISTICS:</b>	Color: Dark Green
	Fragrance: Solvent
	Spray Pattern: 1.00 – 2.00 Full Force Spray @ 6"
	Shelf Life: 1 Year +

<b>REGULATORY:</b>	Recyclable Packaging: Yes
	VOC Compliant CARB/OTC: Yes
	CPSC Flammability: Extremely Flammable
	24 HR. MEDICAL EMERGENCY: 1-866-836-8855

- FEATURES:**
- FORTIFIED WITH MOLY & PTFE
  - CONTAINS NO SILICONES OR CHLORINATED SOLVENTS
  - QUICKLY CUTS THROUGH RUST AND CORROSION



REORDER/ITEM NUMBER SW-689



Manufactured by:  
**SPRAYWAY, INC.**  
 2651 Warrenville Rd. Ste 300 | Downers Grove, IL 60515  
 800-332-9000 • Fax: 630-543-7797 • www.spraywayinc.com