



## SW770 Expandable Insulating Foam Sealant

**DESCRIPTION:** A unique one part urethane foam which expands as it dries and solidifies. Fills cracks and holes that caulk can't! Sprays as a prepolymer then expands and cures to a durable semi-rigid closed cell foam insulation. Each can dispenses over 800 linear feet of product when sprayed in a 3/8 inch cured bead (based on theoretical yield). Forms a water resistant, weather resistant and airtight bond on masonry, wood, metal, glass, and tile. Dries tack free in 10 minutes.

**USES:** An insulating sealant on and around Air Conditioning, Ventilation and Heating Ducts, Plumbing, Window A/C Units, Spas, Hot Tubs, Boats, RV's, Electrical Equipment, Appliances, Refrigeration Units, Carpentry, Masonry, Conversion Vans and Buses, Auto and Truck Doors. Can must be at room temperature for several hours prior to use.

<b>SPECS:</b>	Can Size: 16 oz.
	Net Weight: 12 oz. (340 g)
	Shipping Weight: 13 lbs.
	Packaged: 12 cans per case
	UPC Number: 0 41911 00770 2
	SAP Number: 1000045574

<b>PHYSICAL CHARACTERISTICS:</b>	Color: Creme
	Fragrance: Hydrocarbon
	Spray Pattern: N/A

<b>REGULATORY:</b>	Shelf Life: 1 Year +
	Recyclable Packaging: Yes
	VOC Compliant CARB/OTC: Yes
	CPSC Flammability: Extremely Flammable

24 HR. MEDICAL EMERGENCY: 1-866-836-8855

- FEATURES:**
- CUTS ENERGY COSTS • CONTAINS FLAME RETARDANT
  - FILLS HOLES, SEALS OUT PESTS, DAMPENS SOUND
  - 1" THICKNESS YIELDS R 4-5 INSULATING FACTOR

See label side panel for First Aid and additional precautionary statements.  
**KEEP OUT OF REACH OF CHILDREN. CONSULT SDS BEFORE USING**



REORDER/ITEM NUMBER SW-770

Manufactured by: **SPRAYWAY, INC.**  
2651 Warrenville Rd. Ste 300 | Downers Grove, IL 60515  
800-332-9000 • Fax: 630-543-7797 • www.spraywayinc.com